# **Communication tools**

# Raport 2 software

Manufacturer

Device Type

Hardware revision

Private label distrib

Poling address Preambles

Universal command ravi

C) Identific

2 m

1.0

**RAPORT 2** is a software designed for communication and data transfer from transmitters with Hart or Modbus protocol made by APLISENS.

The communication with the transmitters enables:

- Identification of a transmitter,
- Configuration of its output parameters:
- Reading of a PV values (e.g. pressure, output current, degree of output setting in %).
- Enforcement of output current with a given value,
- Transmitter calibration in relation to master pressure,
- Function linearization (user characteristic creator),
- Zeroing



#### Aplisens Mobile Configurator

**Aplisens Mobile Configurator** is an Android application designed for communication and data transfer from transmitters with Hart or Modbus protocol made by APLISENS. The communication with the transmitters enables:

- Supports wireless Bluetooth connection
- Read basic device information
- Configure device's Tag, Descriptor, Message, Address, etc.
- Monitor process variables
- Configure range and units
- Set/Unset write protection
- Configure specific features of pressure transmitters (LCD, alarms, transfer function, user variable


Sensor serial number		
	Modified 0,Standard,0,0 OK	COMS (SPC)
<b>4</b>		
tor		
	55.	4 (3) 2 and 46 and 6000 44%.
	÷	
	Variables	
	Pv:	0,071 [kPa]
0.071		-0,004 [%] 3,999 [mA]
	Pv Zero	DO PV ZERO
	Lower range (set across of	urrent SET
	pressure)	SEI
-0,004	Upper range (set across o	urrent SET
OPEN VARIABLES PAGE		
	Fixed current mode	
	Current value	
	tor в мес. мине палкал. мине 21,552 22,251 21,500 3,999 -0.04	The second definition of the second definitio

<u>PLISEN</u>

## Hart Field Communicators KAP-03 and KAP-03Ex

#### **Specification:**

The **KAP-03 (KAP-03Ex)** HART field communicator is a portable battery supplied device used for communication and exchange of data with smart transmitters e.g. pressure, differential pressure transmitters. It features an output built as a standard current loop 4-20 mA, using FSK modulation type BEL 202 with an implemented HART communication protocol revision 5 and revision 6. The communicator is specially designed to configure smart transmitters manufactured by APLISENS.



**KAP-03** - standard version **KAP-03Ex** - intrinsic safe version  $\langle \underline{Ex} \rangle$  II 2G Ex ia IIC T4 Gb



SET

### HART/USB converter

**HART/USB converter** allows for connecting and configuration of Hart transmitters via USB port. It works also with devices equipped in Bluetooth.



PIC Engineering And Services (002110838-X) No. 72, Jalan Keluli AN7/AN, Pusat Perniagaan Bukit Raja, Seksyen 7 40000 Shah Alam, Selangor D.E., Malaysia

Shah Alam, Selangor D.E., Malaysia Tel: +6019 338 8819 Fax: +603 3343 8819 Email: <u>sales@picengineering.com.my</u> Website: <u>www.picengineering.com.my</u>

