



KS-Series

Grinding bench for facing fittings and machine components



The KS grinding bench is suitable for surface grinding sliding wedges, valve disks, machine components or other workpieces.

The grinding plate is covered with self-adhesive grinding paper or grinding foil.

A limit stop bar is mounted over the grinding disk to prevent the workpieces that are being machined from sliding away.

This can be secured in different positions depending on the size of the workpieces.

To change the grinding paper rings, the limit stop bar is turned away to the side, thus exposing the grinding disk.

Technical data	KS-6	KS-10
Height	920 mm (36.2")	900 mm (35.4")
Width	650 mm (25.6")	1420 mm (55.9")
Length	900 mm (35.4")	1220 mm (48")
Disk	600 mm (23.6")	1000 mm (39.4")
Weight of workpieces	50 kg	200 kg
Supply voltage	230V/120V 50/60Hz	380-480V 50/60Hz
Power	1,5 kW	3 kW
Rotational speed of disk	20 – 50 rpm	0 – 35 rpm

Accessories

- Footswitch
- 2 Abrasives drawer (KS-6 only)
- Covering hood

The grinding bench's electric drive is equipped with an electronic soft-start system.

A version with quick-change grinding disks is available for use with frequently changing grains (KS-6 only).

Authorize Trading Partner / OEM



PIC Engineering And Services (002110838-X)

No. 72, Jalan Keluli AN7/AN,
Pusat Perniagaan Bukit Raja, Seksyen 7 40000
Shah Alam, Selangor D.E., Malaysia

Tel: +6019 338 8819 Fax: +603 3343 8819
Email: sales@picengineering.com.my
Website: www.picengineering.com.my

